

TOGGLE SWITCH


Toggle Switch



Specifications


Rating: 10A 125V AC; 6A 250V AC / 15A 125V AC; 10A 250V AC / 20A 125V AC; 15A 250V AC | Contact Resistance: 50mΩ Max |
Insulation Resistance: 500VDC 1000M Ω min | Dielectric Strength: 1500V AC for one minute | Operation Temperature: -25°C to +85°C
| Electrical Life: ≥ 10,000 Cycles

T3A-102-112-103-113-123




T3A-102 ON-ON
T3A-112 ON-(ON)
T3A-103 ON-OFF-ON SPDT 3P
T3A-113 ON-OFF-(ON)
T3A-123 (ON)-OFF-(ON)

T3A-101-P




T3A-101-P ON-OFF
SPST-2P

T3A-102-112-103-113-123-P




T3A-102-P ON-ON
T3A-112-P ON-(ON)
T3A-103-P ON-OFF-ON SPDT 3P
T3C-113 ON-OFF-(ON)-A
T3C-123 (ON)-OFF-(ON)-A

T3B-101




T3B-101 ON-OFF
SPST 2P

T3B-102-112-103-113-123




T3B-102 ON-ON
T3B-112 ON-(ON)
T3B-103 ON-OFF-ON SPDT 3P
T3B-113 ON-OFF-(ON)
T3B-123 (ON)-OFF-(ON)

T3B-201




T3B-201 ON-OFF

T3B-202-212-203-213-223



T3B-202 ON-ON
T3B-212 ON-(ON)
T3B-203 ON-OFF-ON DPDT 6P
T3B-213 ON-OFF-(ON)
T3B-223 (ON)-OFF-(ON)

T-32



T-32 ON-ON
DPDT 6P
10A 125VAC; 5A 250VAC