


Ø 22 mm

I-TOP-S1-22B




Diameter: Ø 22mm
 Switch Rating: 5A/250VAC
 Contact Configuration:
 1NO 1NC /2NO 2NC
 Operation Type:
 • Momentary
 • Maintained(Z)
 The Front Shape: Ball
 The Crust Material: Stainless steel
 IP Degree: IP67, IK10



I-TOP-S1-22H




Diameter: Ø 22mm
 Switch Rating: 5A/250VAC
 Contact Configuration:
 1NO 1NC /2NO 2NC
 Operation Type:
 • Momentary
 • Maintained(Z)
 The Front Shape: High
 The Crust Material: Stainless steel
 IP Degree: IP67, IK10



I-TOP-S1-22F-L



Diameter: Ø 22mm
 Color: R, G, Y, O, B, W
 Switch Rating: 5A/250VAC
 Contact Configuration:
 1NO 1NC /2NO 2NC
 Operation Type:
 • Momentary
 • Maintained(Z)
 The Front Shape: Flat
 Lamp type: Dot illuminated (LED)
 The Crust Material: Stainless steel
 IP Degree: IP67, IK10



I-TOP-S1-22F-D



Diameter: Ø 22mm
 Switch Rating: 5A/250VAC
 Contact Configuration:
 1NO 1NC /2NO 2NC
 Operation Type:
 • Momentary
 • Maintained(Z)
 The Front Shape: Flat
 Lamp type: Dot illuminated (LED)
 The Crust Material: Stainless steel
 IP Degree: IP67, IK10

